

SECTION 1 – IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

Product Name:	Ecologic™ Potassium Silicate Paint for Masonry	
Brand:	Ecologic™	
Recommended Use:	Protective Silicate Masonry Coating for Porous Brick, Stone, and Lime Plaster	
Supplier's Details:	LimeWorks.us 3145 State Road Telford, PA 18969	Phone: 215-536-6706 Fax: 215-453-1310 Website: www.limeworks.us
Emergency Phone Number:	InfoTrac 1-800-535-5053	

SECTION 2 – HAZARD IDENTIFICATION

 GHS05 Corrosion	 GHS07 Irritant				
---	--	--	--	--	--

Signal word: Danger

Hazard statements:

H315: Causes skin irritation
 H318: Causes serious eye damage
 H335: May cause respiratory irritation

Precautionary statements:

P102: Keep out of reach of children
 P280: Wear protective gloves/clothing/eye and face protection
 P305+P351+P338+P310: In case of contact with the eyes, rinse carefully with clean water for several minutes. In relevant cases, take off contact lenses if possible. Immediately call a Poison Center or a doctor/physician.
 P302+P352: If in contact with skin: wash abundantly with soap and water.
 P332+P313: For skin irritation: consult a doctor.
 P261+P304+P340: Avoid powder inhalation. In case of inhalation, bring the affected individual outside into fresh air and make the individual relax in a comfortable position for breathing.
 P312: Call a Poison Center in case of general feeling of sickness.

NFPA ratings (scale 0 – 4)

	Health = 1 Fire = 0 Reactivity = 0 Special Notice = None
---	---

HMIS-ratings (scale 0 – 4)

HEALTH 1	Health = 1 Flammability = 0 Physical Hazard = 0 Personal Protection = H
FLAMMABILITY 0	
PHYSICAL HAZARD 0	
PERSONAL PROTECTION H	

Other hazards None known

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

CAS: Various RTECS: Various	Mineral Fillers and Pigments (titanium dioxide, aluminasilicates, iron oxides, earthen pigments) Skin Irrit. 2; Eye Irrit. 2A; STOT SE 3; H315, H319, H335	> 50%
CAS: 7732-18-5 RTECS: Not Available	Water	< 25%
CAS: 1312-76-1 RTECS: Not Available	Liquid Potassium Silicate solution H315, H318, H335	< 25%
CAS: 79-41-4 RTECS: OZ2975000	Methacrylate Dispersion (in > 50% water) Flam. Liq. 4; Acute Tox. 4; Acute Tox. 3; Skin Corr. 1A; Eye Dam. 1; STOT SE 3; Aquatic Acute 3; H227, H302 + H332, H311, H314, H318, H335, H402	< 10%
CAS: 01336-21-6 RTECS: BQ9625000	Ammonia Solution H302, H314, H318, H400	< 1%
CAS: 1310-73-2 RTECS: TT2975000	Sodium Phosphonate Stabilizer	< 1%
CAS: 9004-34-6 RTECS: FJ5950200	Polysaccharide, Cellulose	< 1%
CAS: 126-71-6 RTECS: TC9300000	Fatty Acid Defoamer H317, H412	< 1%

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4 – FIRST AID MEASURES

Inhalation:	Remove source of contamination or have person move to fresh air. If not breathing, give artificial respiration. Obtain medical attention immediately.
Skin Contact:	Wash contaminated area with running water for at least 15-20 minutes, while removing contaminated clothing. Obtain medical attention. Launder contaminated clothing before re-use.
Eye Contact:	Immediately flush the contaminated eye(s) with gently flowing water for at least 15-20 minutes. Obtain medical attention.
Ingestion:	NEVER give anything by mouth if the person is rapidly losing consciousness, or is unconscious, or convulsing. Rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Repeat administration of water. Obtain Medical attention immediately.

SECTION 5 – FIRE FIGHTING MEASURES

Fire Hazards/Conditions of Flammability:	This product is not flammable or combustible
Flash Point (Method):	Not Determined
Lower Flammable Limit (% by volume):	Not Determined
Upper Flammable Limit (% by volume):	Not Determined
Sensitivity to Mechanical Impact:	Probably not sensitive.
Sensitivity to Static Discharge:	Probably not sensitive.
Auto-Ignition Temperature:	Not Determined
Suitable Extinguishing Media:	Carbon dioxide, dry chemical powder, and appropriate foam for surrounding products.
Special Fire-Fighting Procedures/Equipment:	During a fire, irritating/toxic smoke and fumes may be generated by surrounding products. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece.
Hazardous Combustion Products:	Carbon oxides, other irritating fumes, and smoke generated by surrounding products

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. Remove all ignition sources. Remove or isolate flammable and combustible materials. All persons dealing with clean-up should wear the appropriate protective equipment (See section 8).
Environmental Precautions:	Confine spill, preventing it from entering sewer lines or waterways. Dispose of as per local, state, and federal regulations
Spill Response / Cleanup:	Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product Notify the appropriate authorities as required.

SECTION 7 – HANDLING AND STORAGE

Safe Handling Procedures:	Before handling, it is very important that engineering controls are operating, and that protective equipment requirements, and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Handling equipment should be properly grounded. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dusts. Avoid contact with eyes, skin, and clothing. Avoid generating high concentrations of dusts. Keep away from incompatible materials such as strong oxidizing materials. Keep containers closed when not in use.
Storage Requirements:	Store in a cool, dry, well-ventilated area out of direct sunlight. Store away from incompatible materials. Inspect all incoming containers to make sure they are properly labeled and not damaged. Storage area should be clearly identified, clear of obstruction, and accessible only to trained personnel. Inspect periodically for damage or leaks.
Incompatible Materials:	STRONG OXIDIZING MATERIALS, strong acids, some metals.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:	There is no available data for the product. See below for individual ingredient exposure limits.			
Ingredient	OSHA PEL		ACGIH TLV	
	TWA	STEL	TWA	STEL
Water	Not Determined	Not Determined	Not Determined	Not Determined
Mineral Fillers and Pigments	Not Determined	Not Determined	Not Determined	Not Determined
Liquid Potassium Silicate solution	Not Determined	Not Determined	Not Determined	Not Determined
Methacrylate Dispersion (in > 50% water)	Not Determined	Not Determined	Not Determined	Not Determined
Ammonia Solution	Not Determined	Not Determined	Not Determined	Not Determined
Sodium Phosphonate Stabilizer	Not Determined	Not Determined	Not Determined	Not Determined
Polysaccharide, Cellulose	Not Determined	Not Determined	Not Determined	Not Determined
Fatty Acid Defoamer	Not Determined	Not Determined	Not Determined	Not Determined

Engineering Controls:	Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits.
Respiratory Protection:	Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirator if the exposure limits are unknown.
Protective Clothing/Equipment:	Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mist and dust from entering the eyes. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.
General Hygiene Considerations:	Avoid generating high concentrations of dusts. Avoid contact with skin and eyes. Avoid breathing dusts or mists. Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical State, Color, Etc:	Milky color, but dries clear.	Upper / lower flammability or explosive limits:	Not Determined
Odor:	Light ammonia odor only while still wet.	Vapor Pressure:	Not Determined
Odor Threshold:	Not Determined	Vapor Density:	Not Determined
pH:	8.5 – 9.5	Relative Density:	Not Determined
Melting / Freezing Point:	Not Determined	Solubility(ies):	Slightly in water
Initial Boiling Point and Boiling Range:	Not Determined	Partition Coefficient: n-octanol/water:	Not Determined
Flash Point:	Not Determined	Auto-Ignition Temperature:	Not Determined
Evaporation Rate:	Not Determined	Decomposition Temperature:	Not Determined
Flammability (solid, gas):	Not Determined	Viscosity:	Not Determined

SECTION 10 – STABILITY AND REACTIVITY DATA

Reactivity:	Not Determined
Chemical Stability:	Stable under the recommended storage and handling conditions prescribed.
Possibility of Hazardous Reactions:	Hazardous polymerization will not occur.
Conditions to Avoid:	Incompatible materials (see Section 7).
Incompatible Materials:	Incompatible materials (see Section 7).
Hazardous Decomposition Products:	Hazardous combustion products (see Section 5).

SECTION 11 – TOXICOLOGICAL INFORMATION

Routes of Exposure:	Eye contact, ingestion, inhalation, skin contact.	
Effects of Short-Term (Acute) Exposure:		
Eyes:	Direct eye contact may cause moderate eye irritation or burn. Symptoms may include redness, stinging, tearing, and pain.	
Ingestion:	Ingestion may cause irritation or burn to the mouth, throat, and stomach. Symptoms may include dizziness, drowsiness, nausea, headache, and other central nervous system effects.	
Inhalation:	May cause irritation or burn to the nose, throat, and respiratory tract. Symptoms may include burning sensation, sore throat, runny nose, coughing, wheezing, shortness of breath, and difficulty breathing.	
Skin:	Direct skin contact may cause moderate to severe irritation or burn.	
Effects of Long-Term (Chronic) Exposure:		
	Not Determined	
Other Important Hazards:	Not Determined	
Numerical Measures of Toxicity:		
Ingredient	CAS # and RTECS #	LD₅₀ (route, species)
Water	CAS: 7732-18-5 RTECS: Not Available	7,340 mg/kg Oral, Rat
Mineral Fillers and Pigments	CAS: Various RTECS: Various	6,450 mg/kg Oral, Rat
Liquid Potassium Silicate solution	CAS: 1312-76-1 RTECS: Not Available	Not Determined
Methacrylate Dispersion (in > 50% water)	CAS: 79-41-4 RTECS: OZ2975000	Not Determined
Ammonia Solution	CAS: 01336-21-6 RTECS: BQ9625000	Not Determined
Sodium Phosphonate Stabilizer	CAS: 1310-73-2 RTECS: TT2975000	Not Determined
Polysaccharide, Cellulose	CAS: 9004-34-6 RTECS: FJ5950200	Not Determined
Fatty Acid Defoamer	CAS: 126-71-6 RTECS: TC9300000	Not Determined

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity:	There is no available data on the product itself.
Persistence and Degradability:	Not Determined
Bioaccumulative Potential:	Not Determined
Mobility in the Soil:	Not Determined
Other Adverse Effects:	Not Determined

SECTION 13 – WASTE DISPOSAL

Disposal must be in accordance with National or Local legislation and directives.
 Bags are exclusively for containing the product and must not be utilized for other use.
 Dispose of the contents and bags at a point of refuse collection.
 Harden the product before disposal by wetting it. Bags should be totally emptied.

SECTION 14 – TRANSPORTATION INFORMATION

UN Number	Non-Regulated Material	Environmental Hazards	Not Applicable
UN Proper Shipping Name	Non-Regulated Material	Transport in Bulk	Not Applicable
Transport Hazard Class(es)	Non-Regulated Material	Special Precautions	Not Applicable
Packing Group	Non-Regulated Material		

SECTION 15 – REGULATORY INFORMATION

OSHA Information:	This product is regulated according to OSHA. This SDS contains all the information required by OSHA.				
TSCA Information:	The ingredients in this product are listed on the TSCA.				
National Fire Protection Association (NFPA):					
HEALTH: 1	FLAMMABILITY: 0	INSTABILITY: 0	SPECIAL HAZARDS: Refer to Section 1 & 3		
HAZARD SCALE:	0 = Minimal	1 = Slight	2 = Moderate	3 = Serious	4 = Severe
New Jersey Labeling Requirements:	Ingredients to be disclosed on product labeling: Refer to Section 3.				
California Proposition 65:	This product does not contain chemicals that are known to the State of California to cause cancer or other reproductive harm.				

SECTION 16 – OTHER INFORMATION

References:	1. Safety Data Sheets from manufacturer/supplier.		
Abbreviations:			
ACGIH	American Conference of Governmental Industrial Hygienists	NTP	National Toxicology Program
AIHA	American Industrial Hygiene Association	OSHA	Occupational Safety and Health Administration
CAS	Chemical Abstract Service	PEL	Permissible Exposure Limit
DSL	Domestic Substance List	STEL	Short-term Exposure Limit
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
LC	Lethal Concentration	TSCA	Toxic Substances Control Act
LD	Lethal Dosage	TWA	Time Weighted Average
N/A	Not Applicable/Not Available	WHMIS	Workplace Hazardous Materials Information System
NIOSH	National Institute for Occupational Safety and Health		
H227	Combustible liquid		
H302	Harmful if swallowed		
H311	Toxic in contact with skin		
H314	Causes severe skin burns and eye damage		
H315	Causes skin irritation		
H317	May cause an allergic skin reaction		
H318	Causes serious eye damage		
H319	Causes serious eye irritation		
H332	Harmful if inhaled		
H335	May cause respiratory irritation		
H400	Very toxic to aquatic life		
H402	Harmful to aquatic life		
H412	Harmful to aquatic life with long-lasting effects		

To be best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. End of the SDS.