> AOX-S Rotation Mixer





> Materials and applications





· Grout ·











AOX-S rotation mixer

- Compact, light and easy to transport. One person can easily handle transporting this machine.
- Productivity: interchangable buckets increase productivity while short mixing times encable high hourly throughput.
- Best workability thanks to completely mixed material.
 This supports the optimal effectiveness of the building material
- Interchangable mixing tools for a wide range of materials with different viscosities to work with. Rim scraper to prevent material deposits on the side of the bucket.
- Health and safety: Safety shutdown as soon as the machine is opened. A dust extractor can be connected.
- A transport trolley is available as an accessory for transporting the buckets
- Ideal for tile and reinforcing adhesives, fillers, slurries, mortars, stucco, leveling compounds and much more
- The practical assistant for tilers, floor layers, masons, painters, restorers, etc.



Material to mix with	the choosen n	addle:	DLX	KR

Cement mortar		•
Fillers		0
Stucco		0
Natural stone mortar/cobblestone mortar		0
Soft 2K pavement grout	0	0
Natural stone mortar		0
Tile adhesive		0
Grout	•••••	0
Thin-bed mortar, flat stone adhesive	0	
Bonding agents	0	
Joint-sealing compounds		•
2-K sealing slurry	0	
Levelling compounds	0	
2-K epoxy resin sand mixture, soft		•

Technical data

Mixing quantity:	up to 10 gal.	
Bucket capacity:	17 gal.	
Mixing tool output:	1.3 hp / 110 V	
Mixing tool, on-load speed:	610 rpm	
Bucket speed:	18 rpm	
Weight (empty):	112.5 lbs	
Dimensions:	23.6" x 32.2" x 34.3"	
AOX-S item no.:	AOXS	
DLX mixing tool item no.:	DLX Mixing tool	
KR mixing tool item no.:	KR Mixing tool	
Accessories		
17 gal. mixing bucket item no.:	17GB	
Bucket Dolly (option) item no.:	BC17	

Your Collomix specialised dealers:



Product video









15499-040 © Collomix 2020