

ecologic®

Mortar & Plaster

Mortar & Plaster
For Historic Restoration
and Green Building

www.Lime Works.us

Last Modified: January 3, 2023

EasyMeshTM Fiberglass Mesh Tape

Self-Adhering, Non-Rusting, Alkali-Resistant Fiberglass Mesh Tape for Lime Plaster/Stucco Systems



PRODUCT SPECIFICATIONS:

• Packaging: Single Roll

• Color: Blue

• *Roll Size:* 23/8" x 150' (6 cm x 91.44 m)

• *Roll Weight:* 0.9 lbs (0.41 kg)

Mesh Weight (after coat): 2.2 oz/yd² (75 g/m²)
 Mesh Weight (before coat): 1.6 oz/yd² (52 g/m²)

• Weave Type: Leno

• *Weave Eye:* 0.11" x 0.11" (0.28 x 0.28 cm)

• *Warp:* 134 x 1 x 2 tex

Weft: 300 texTensile Strength:

Warp: 160 lbs/in (0.794 kg/cm) Weft: 183 lb/in (0.908 kg/cm)

• Alkali Resistance: Grade A

50% retention rate for tensile fracture strength after 28-day immersion in 5% Na(OH) solution.

EasyMeshTM is a product of Drywall Specialties Corp.
111 Bromleigh Rd, Stewart Manor, NY 11530.
Phone: 718-628-6142

Fax: 718-628-0237

PRODUCT DESCRIPTION:

Self-adhering blue alkaline resisting mesh tape incorporates an extra strength adhesive on one side for easy use as a supplement in plaster systems to help prevent cracking, reinforce corners, or provide a back for ornamental plaster.

USES:

Use for crack overly in the repair of fine and sporadic faults in gypsum or lime plaster, or cement or lime stucco/renders. Ideal for use with EcologicTM Plaster TAKCOATTM or TOP-COATTM systems to permanently hide joints, cracks, holes, and/or unify surfaces without the need to embedded into mortar or plaster.

For spanning over wider areas, consider using EcologicTM Brand Fiberglass Mesh Tape available in 6" width or self-adhering EcologicTM Brand Fiberglass Mesh Roll in 18" width.

For covering whole walls when embedding into an EcologicTM Brand Lime Plaster System, use non-adhesive EcologicTM Brand Fiberglass Mesh Roll available in 9.5" and 38" widths.

All LimeWorks. us publications are offered on a complementary basis and as a general guide for our customers without guarantee to the accuracy or completeness of any information contained in them. The purchaser is solely responsible to determine the suitability of any LimeWorks. us product for any intended use and purpose.

CONTACT:

Lime Works. us 3145 State Road Telford, PA 18969 www.Lime Works.us

Phone: 215-536-6706 **Fax:** 215-453-1310

Email: info@LimeWorks.us