

Safety Data Sheet

Ecologic[™] LimeWash Platinum

| Product Name: Ecologic™ LimeWash Platinum | | | | | |
|---|---|--|---|---|--|
| Brand: | | Ecologic™ | | | |
| Recommended Use | : | A Lime to be put in a potable water solution to make a decorative paint coating for masonry | | | |
| Supplier's Details: | | Lime <i>Works</i> .us 3145 State Road Telford, PA 18969 | Fax: 215-453 | Phone: 215-536-6706 Fax: 215-453-1310 Website: www.limeworks.us | |
| Emergency Phone Number: | | InfoTrac 1-800-535-5053 | | | |
| | | | | | |
| SECTION 2 – HA | ZARD IDENTIFI | CATION | | | |
| GHS05 Corrosion | GHS07 Irritant | GHS08 Health Hazard | | | |
| Signal word: Dange | r | | | | |
| Hazard statements: | | | | | |
| H315: Causes skin in H318: Causes seriou H335: May cause res | s eye damage | | | | |
| Precautionary state | ments: | | | | |
| off contact lenses if p P302+P352: If in con P332+P313: For skin P261+P304+P340: A individual relax in a c P312: Call a Poison (| e gloves/clothing/eye P310: In case of conta ossible. Immediately tact with skin: wash a i irritation: consult a c void powder inhalatio omfortable position f Center in case of ger gs content/empty bag and bags should be | act with the eyes, rinse carefully w call a Poison Center or a doctor/p abundantly with soap and water. doctor. on. In case of inhalation, bring the or breathing. neral feeling of sickness. gs at a point of refuse collection. B | hysician. affected individual outside ir | to fresh air and make the | |
| | | | | | |
| | Health = 3 Fire = 0 Reactivity = 0 Special Notice = None | | | | |
| HMIS-ratings (scale | 0 - 4) | | | | |
| HEALTH3FLAMMABILITY0PHYSICAL0HAZARD0 | Health = 3 Flammability = 0 Physical Hazard = Personal Protection | | | | |

SDS Preparation / Review Date: Jul 21, 2020



Safety Data Sheet

Ecologic[™] LimeWash Platinum

| PERSONAL PROTECTION | | | |
|------------------------|------------------|---------------------------|------|
| Other hazards | None known | | |
| SECTION 3 – C | OMPOSITION / INF | ORMATION ON INGREDIENTS | |
| CAS# 1305-62-0 | | Calcium Hydroxide | >90% |
| CAS# 14808-60-7 | | Silica-crystalline quartz | <1% |
| CAS# 10043-01-3 | | Aluminum Sulfate (Alum) | 5-6% |
| | | Trace Additives | <5% |

May also contain ~1 of less of Magnesium oxide, Potassium oxide, Sodium oxide, Ferric oxide, ... * May exceed the limit ...

| SECTION 4 - | SECTION 4 – FIRST AID MEASURES | | |
|---------------|--|--|--|
| Inhalation: | Remove source of contamination or have person move to fresh air. If not breathing, give artificial respiration. Obtain medical attention immediately. | | |
| Skin Contact: | Wash contaminated area with running water for at least 15-20 minutes, while removing contaminated clothing. Obtain medical attention. Launder contaminated clothing before re-use. | | |
| Eye Contact: | Immediately flush the contaminated eye(s) with gently flowing water for at least 15-20 minutes. Obtain medical attention. | | |
| Ingestion: | NEVER give anything by mouth if the person is rapidly losing consciousness, or is unconscious, or convulsing. Rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Repeat administration of water. Obtain Medical attention immediately. | | |

| SECTION 5 – FIRE FIGHTING MEASURES | | |
|--|--|--|
| Fire Hazards/Conditions of Flammability: | This product is not flammable or combustible | |
| Flash Point (Method): | Not Determined | |
| Lower Flammable Limit (% by volume): | Not Determined | |
| Upper Flammable Limit (% by volume): | Not Determined | |
| Sensitivity to Mechanical Impact: | Probably not sensitive. | |
| Sensitivity to Static Discharge: | Probably not sensitive. | |
| Auto-Ignition Temperature: | Not Determined | |
| Suitable Extinguishing Media: | Carbon dioxide, dry chemical powder, and appropriate foam for surrounding products. | |
| Special Fire-Fighting Procedures/Equipment: | During a fire, irritating/toxic smoke and fumes may be generated by surrounding products. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. | |
| Hazardous Combustion Products: | Carbon oxides, other irritating fumes, and smoke generated by surrounding products | |

SECTION 6 – ACCIDENTAL RELEASE MEASURES Personal Precautions: Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. Remove all ignition sources. Remove or isolate flammable and



Safety Data Sheet Ecologic™ LimeWash Platinum

| | combustible materials. All persons dealing with clean-up should wear the appropriate protective equipment (See section 8). |
|----------------------------|--|
| Environmental Precautions: | Confine spill, preventing it from entering sewer lines or waterways. Dispose of as per local, state, and federal regulations |
| Spill Response / Cleanup: | Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product Notify the appropriate authorities as required. |

| SECTION 7 – HANDLING AND STORAGE | | |
|----------------------------------|--|--|
| Safe Handling Procedures: | Before handling, it is very important that engineering controls are operating, and that protective equipment requirements, and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Handling equipment should be properly grounded. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dusts. Avoid contact with eyes, skin, and clothing. Avoid generating high concentrations of dusts. Keep away from incompatible materials such as strong oxidizing materials. Keep containers closed when not in use. | |
| Storage Requirements: | Store in a cool, dry, well-ventilated area out of direct sunlight. Store away from incompatible materials. Inspect all incoming containers to make sure they are properly labeled and not damaged. Storage area should be clearly identified, clear of obstruction, and accessible only to trained personnel. Inspect periodically for damage or leaks. | |
| Incompatible Materials: | STRONG OXIDIZING MATERIALS, strong acids, some metals. | |

| Exposure Limits: | There is no available data for the product. See below for individual ingredient exposure limits. | | | its. | |
|-----------------------------|--|---|----------------|--------------------------------|----------------|
| Ingredient | | OSHA | PEL ACGIH TLV | | H TLV |
| | | TWA | STEL | TWA | STEL |
| Calcium Hydroxide | | 15 mg/m ³ | Not Determined | 10 mg/m ³ | Not Determined |
| Crystalline Silica | | 10 mg/m³ _† (resp.) %SiO ₂ +2 | Not Determined | .1 mg/m ³ † (resp.) | Not Determined |
| Phthalocyanine Bluing Agent | | Not Determined | Not Determined | Not Determined | Not Determined |
| Casein | | Not Determined | Not Determined | Not Determined | Not Determined |
| Aluminum Sulfate (Alum) | | 2 mg/m ³ | Not Determined | 2 mg/m ³ | Not Determined |
| Sodium Tetraborate (Borax) | | 10 mg/m ³ | Not Determined | 10 mg/m ³ | Not Determined |

* Respirable fraction.

** Crystalline silica is expected to be below 1%, but concentrations may vary with source material

[†] The OSHA Permissible Exposure Limit (PEL) for Silicon Dioxide (SiO₂) is dependent upon the percentage of free silica in the dust and is calculated by a formula given.

| Engineering Controls: | Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. |
|--------------------------------|---|
| | Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirator if the exposure limits are unknown. |
| Protective Clothing/Equipment: | Chemically protective gloves (impervious), and other protective clothing to prevent |

SDS Preparation / Review Date: Jul 21, 2020

Get the latest version at Lime*Works*.us



Safety Data Sheet Ecologic™ LimeWash Platinum

| | prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mist and dust from entering the eyes. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area. |
|---------------------------------|--|
| General Hygiene Considerations: | Avoid generating high concentrations of dusts. Avoid contact with skin and eyes. Avoid breathing dusts or mists. Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use. |

| SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES | | | |
|--|----------------|---|-------------------|
| Physical State, Color, Etc: | White powder | Upper / lower flammability or explosive limits: | Not Determined |
| Odor: | Odorless | Vapor Pressure: | Not Determined |
| Odor Threshold: | Not Determined | Vapor Density: | Not Determined |
| pH: | ~12.3 | Relative Density: | Not Determined |
| Melting / Freezing Point: | Not Determined | Solubility(ies): | Slightly in water |
| Initial Boiling Point and Boiling Range: | Not Determined | Partition Coefficient: n-octanol/water: | Not Determined |
| Flash Point: | Not Determined | Auto-Ignition Temperature: | Not Determined |
| Evaporation Rate: | Not Determined | Decomposition Temperature: | Not Determined |
| Flammability (solid, gas): | Not Determined | Viscosity: | Not Determined |

| SECTION 10 – STABILITY AND REACTIVITY DATA | | |
|--|--|--|
| Reactivity: | Not Determined | |
| Chemical Stability: | Stable under the recommended storage and handling conditions prescribed. | |
| Possibility of Hazardous Reactions: | Hazardous polymerization will not occur. | |
| Conditions to Avoid: | Incompatible materials (see Section 7). | |
| Incompatible Materials: | Incompatible materials (see Section 7). | |
| Hazardous Decomposition Products: | Hazardous combustion products (see Section 5). | |

| SECTION 11 – TOXICOLOGICAL INFORMATION | | | | |
|---|---|---|--|--|
| Routes of Exposure: | | Eye contact, ingestion, inhalation, skin contact. | | |
| Effects of Short-Term (Acute) Exposure: | | | | |
| Eyes: | Direct eye contact m tearing, and pain. | Direct eye contact may cause moderate eye irritation or burn. Symptoms may include redness, stinging, tearing, and pain. | | |
| Ingestion: | | Ingestion may cause irritation or burn to the mouth, throat, and stomach. Symptoms may include dizziness, drowsiness, nausea, headache, and other central nervous system effects. | | |
| Inhalation: | | May cause irritation or burn to the nose, throat, and respiratory tract. Symptoms may include burning sensation sore throat, runny nose, coughing, wheezing, shortness of breath, and difficulty breathing. | | |
| Skin: | Direct skin contact m | Direct skin contact may cause moderate to severe irritation or burn. | | |
| Effects of Long- | -Term (Chronic) Exposur | e: | | |
| Inhalation: | | Prolonged inhalation of crystalline silica may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs, a dry cough, shortness of breath, emphysema, decreased | | |



Safety Data Sheet Ecologic[™] LimeWash Platinum

chest expansion, and increased susceptibility to tuberculosis. In advanced stages, loss of appetite, pleuritic pain, and total incapacity to work. Advanced silicosis may result in death due to cardiac failure or destruction of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP. – Based on Human Evidence

| Other Important Hazards: | Not Determined | Not Determined | | |
|----------------------------------|-----------------|---|--|--|
| Numerical Measures of Toxicity*: | | | | |
| Ingredient | CAS # | LD₅₀ (route, species) | | |
| Calcium Hydroxide | CAS# 1305-62-0 | 7340 mg/kg (oral, rat) | | |
| Crystalline Silica | CAS# 14808-60-7 | 22,500 mg/kg (oral, rat) | | |
| Aluminum Sulfate (Alum) | CAS# 10043-01-3 | 410 mg/kg (unreported, rat); 6207 mg/kg (oral, mouse); 274 mg/kg (intraperitoneal, mouse); 520 mg/kg (unreported, mouse); 490 mg/kg (unreported, guinea pig) | | |

*Individual toxicity levels of component ingredients only, not documented in combination for the product itself.

| SECTION 12 – ECOLOGICAL INFORMATION | | |
|-------------------------------------|---|--|
| Ecotoxicity: | There is no available data on the product itself. | |
| Persistence and Degradability: | Not Determined | |
| Bioaccumulative Potential: | Not Determined | |
| Mobility in the Soil: | Not Determined | |
| Other Adverse Effects: | Not Determined | |

SECTION 13 – WASTE DISPOSAL

Disposal must be in accordance with National or Local legislation and directives. Bags are exclusively for containing the product and must not be utilized for other use. Dispose of the contents and bags at a point of refuse collection. Harden the product before disposal by wetting it. Bags should be totally emptied.

| SECTION 14 – TRANSPORTATION INFORMATION | | | |
|---|---------------------------|-----------------------|----------------|
| UN Number | Non-Regulated Material | Environmental Hazards | Not Applicable |
| UN Proper Shipping Name | Non-Regulated Material | Transport in Bulk | Not Applicable |
| Transport Hazard Class(es) | Non-Regulated Material | Special Precautions | Not Applicable |
| Packing Group | Non-Regulated Material | | |

| SECTION 15 – REGULATORY INFORMATION | | |
|--|--|--|
| OSHA Information: This product is regulated according to OSHA. This SDS contains all the information required by OSHA. | | |
| TSCA Information: The ingredients in this product are listed on the TSCA. | | |
| National Fire Protection Association (NFPA): | | |

SDS Preparation / Review Date: Jul 21, 2020

Get the latest version at LimeWorks.us



Safety Data Sheet

Ecologic[™] LimeWash Platinum

| HEALTH: 3 | FLAMMABILITY: 0 | INSTABILITY: 0 | SPECIAL HAZARDS: Refer to Section 1 & 3 | | | |
|---|-----------------|---|--|--------------------------|-----------------|--|
| HAZARD SCALE: | 0 = Minimal | 1 = Slight | 2 = Moderate | 3 = Serious | 4 = Severe | |
| New Jersey Labeling Requirements: Ingredients t | | Ingredients to be disc | ients to be disclosed on product labeling: Refer to Section 3. | | | |
| | | This product contains cancer or other repro | chemicals that are kno ductive harm. | own to the State of Cali | fornia to cause | |

| SECTION 16 - | - OTHER INFORMATION | | | |
|----------------|--|---|---|--|
| References: | 1. Safety Data Sheets from manufacturer/s | 1. Safety Data Sheets from manufacturer/supplier. | | |
| Abbreviations: | | | | |
| ACGIH | American Conference of Governmental Industrial Hygienists | NTP | National Toxicology Program | |
| AIHA | American Industrial Hygiene Association | OSHA | Occupational Safety and Health Administration | |
| CAS | Chemical Abstract Service | PEL | Permissible Exposure Limit | |
| DSL | Domestic Substance List | STEL | Short-term Exposure Limit | |
| IARC | International Agency for Research on Cancer | TLV | Threshold Limit Value | |
| LC | Lethal Concentration | TSCA | Toxic Substances Control Act | |
| LD | Lethal Dosage | TWA | Time Weighted Average | |
| N/A | Not Applicable/Not Available | WHMIS | Workplace Hazardous Materials Information System | |
| NIOSH | National Institute for Occupational Safety and Health | | | |
| H315 | Causes skin irritation | Causes skin irritation | | |
| H318 | Causes serious eye damage | Causes serious eye damage | | |
| H319 | Causes serious eye irritation | Causes serious eye irritation | | |
| H335 | May cause respiratory irritation | | | |
| H350 | May cause cancer | | | |
| H372 | Causes damage to organs through prolonged or repeated exposure | | | |
| H402 | Harmful to aquatic life | Harmful to aquatic life | | |

To be best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. End of the SDS.